

RECORD OF LAND CORNER MONUMENTATION


CORNER: S $\frac{1}{4}$ Cor. Sec. 13, T.17S., R.31E., W.M.

ORIGINAL SURVEY BY: Rueben R. Leigh

CONTRACT NUMBER: 489

CONTRACT DATE: August 15, 1883

SUBSEQUENT SURVEY: Scott R. McIntyre 1979



ORIGINAL G.L.O. DESCRIPTION: Set a post 3 $\frac{1}{2}$ ft. long 3 ins. square with marked stone 24 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N. face from which: A pine 14 ins. dia. bears S15°E., 42 lks. dist. marked $\frac{1}{4}$ S BT. A pine 12 ins. dia. bears S80°W., 75 lks dist. marked $\frac{1}{4}$ S BT.

1979 RESURVEY BY SCOTT R. MCINTYRE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 05/21/1979 (Pg 358-359): SEE RECORD MAP OF SURVEY NO. 752.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, determined at record bearing and distance from the remains of an original bearing tree:

A decayed pine stump, 14 ins. diam., bears S. 15° E., 42 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.

T 17 S R 31 E
 $\frac{1}{4}$ S 13
S 24
1979

from which

A pine, 12 ins. diam., bears S. 23° E., 63 lks. dist., mkd. $\frac{1}{4}$ S24 BT.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 752 filed in the Grant County Surveyor's Office.

PREPARED BY:

Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251


December 23, 2016

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 27 2016

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2018