

RECORD OF LAND CORNER MONUMENTATION


CORNER: W $\frac{1}{4}$ Cor. Sec. 22, T.17S., R.31E., W.M.

ORIGINAL SURVEY BY: Samuel L. Lackland

CONTRACT NUMBER: 197

CONTRACT DATE: May 29, 1881

SUBSEQUENT SURVEY: Scott R. McIntyre 1979



ORIGINAL G.L.O. DESCRIPTION: Set stone 20X20X12 in mound of stone for $\frac{1}{4}$ sec. cor. from which:
A pine 24 in. dia. bears S.30°W., 22 lks. dist.

1979 RESURVEY BY SCOTT R. MCINTYRE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 05/21/1979 (Pg. 381): SEE RECORD MAP OF SURVEY NO. 752.

The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented with the original basalt stone, 20 x 20 x 12 ins., firmly set 6 ins. in the ground, in a collar of stone, mkd. $\frac{1}{4}$ on W. face, from which the remaining original bearing tree:

A pine, 34 ins. diam., bears S. 30° W., 22 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 17 S R 31 E
 $\frac{1}{4}$
S 21 | S 22
1979

from which a new bearing tree

A fir, 15 ins. diam., bears N. 38° E., 29 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 752 filed in the Grant County Surveyor's Office.

PREPARED BY:

Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251

December 20, 2016

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 28 2016

BY: 



EXPIRES: 6/30/2018