

RECORD OF LAND CORNER MONUMENTATION


CORNER: SE Cor. Sec. 23, T.17S., R.31E., W.M.

ORIGINAL SURVEY BY: Rueben R. Leigh

CONTRACT NUMBER: 489

CONTRACT DATE: August 15, 1883

SUBSEQUENT SURVEY: Scott R. McIntyre 1979



ORIGINAL G.L.O. DESCRIPTION: Set a basalt stone 16x14x10 ins. 11 ins. in ground for cor. to secs. 23, 24, 25, & 26 marked with 2 notches on S. and 1 notch on E. edges and raised a mound of stone 3½ ft. high 4½ ft. base alongside.

1979 RESURVEY BY SCOTT R. MCINTYRE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 05/21/1979 (Pg. 355): SEE RECORD MAP OF SURVEY NO. 752.

Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, supported in a mound of stone, 6 ft. base, to top, with brass cap mkd.

T 17	S R 31 E
S 23	S 24
S 26	S 25
1979	

from which

A pine, 20 ins. diam., bears N. 66° E., 96 lks. dist., mkd. T17S R31E S24 BT.

A pine, 16 ins. diam., bears S. 30° E., 67 lks. dist., mkd. T17S R31E S25 BT.

A pine, 16 ins. diam., bears S. 80° W., 226½ lks. dist., mkd. T17S R31E S26 BT.

A pine, 14 ins. diam., bears N. 56° W., 116 lks. dist., mkd. T17S R31E S23 BT.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 752 filed in the Grant County Surveyor's Office.

PREPARED BY:


Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251


December 21, 2016

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 28 2016

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2018