

RECORD OF LAND CORNER MONUMENTATION


CORNER: S $\frac{1}{4}$ Cor. Sec. 26, T.17S., R.31E., W.M.

ORIGINAL SURVEY BY: Samuel L. Lackland

CONTRACT NUMBER: 197

CONTRACT DATE: May 29, 1881

SUBSEQUENT SURVEY: Scott R. McIntyre 1979



ORIGINAL G.L.O. DESCRIPTION: Set stone 18x10x4 in mound of stone for $\frac{1}{4}$ sec. cor.

1979 RESURVEY BY SCOTT R. MCINTYRE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 05/21/1979 (Pg 364): SEE RECORD MAP OF SURVEY NO. 752.

The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with the original unmarked basalt stone, 15 x 10 x 4 ins. (record, 18 x 10 x 4 ins.) loosely set 4 ins. in the ground, in an embedded collar of stone.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.

T 17 S R 31 E
 $\frac{1}{4}$ S 26
S 35
1979

from which

A pine, 18 ins. diam., bears N. 11° E., 121 lks.
dist., mkd. $\frac{1}{4}$ S26 BT.

A pine, 18 ins. diam., bears S. 14° W., 126 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S35 BT.

Deposit corner stone alongside iron post.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 752 filed in the Grant County Surveyor's Office.

PREPARED BY:


Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251


December 21, 2016

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 28 2016

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2018