(62)
5

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by Henry W. Cooke
under General Land Office contract #494

Surveyor General record states;

Set basalt stone 16x14x8 ins. for ¼ sec.cor. marked
¼ on N. face from which;

A Pine 48 ins. diam. bears S10W, 49 lks.
A Pine 48 ins. diam. bears N5W, 175 lks.

DIAGRAM

¼ S 5 / S 8

T17S R32E

No record of subsequent remonumentation was found in the County records

Description of corner evidence found:

Found marked stone 16x14x8 at base of 8 inch P.Pine
Found 1 BT and 1 stump hole

See map of survey dated October 1981

Description of monument and accessories I established to perpetuate the original location of this corner:

Stone is at base of 8 inch P.Pine which is beginning to grow around stone
I therefor mark this tree as the ¼ corner, marked ¼ S5 on the North face
and S8 on the South face from which;

ORIGINAL BTs
A 44 inch P.Pine stump bears N1W, 115.5 feet, scribes visible
A stump hole bears S10W, 32± feet

NEW BTs
A 12 inch P.Pine bears N49E, 53.4 feet marked ¼ S5 BT
A 10 inch P.Pine bears S6E, 24.0 feet, marked ¼ S8 BT

Buried stone South and alongside tree.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1964
DUANE I. GRIFFITH
644

Date. September 13, 1981
Brass washer nailed to BT blaze. Used steel tape and magnetic compass with 21° East declination in the establishment of accessories. Original BTs measured to face of blaze. New BTs measured to center of tree.

Office of Lakeview *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 23 *day of* Dec, *19* 81
Robert D. Leggett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

E-7