

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. V-3

History of original corner establishment:

This corner was originally established by Henry W. Cooke in 1884 under GLO Contract Number 494. Surveyor General Field Notes state:

Set a basalt stone 16x10x5 ins. - 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on the N. face and raised a mound of stone 1 1/2 ft. high and 3 1/2 ft. base alongside.

DIAGRAM

T17S R32E  
S30  
1/4 \_\_\_\_\_  
S31  
1992  
PLS 848

Description of Corner Evidence Found:

Found stone of near record size (16x10x5 ins.) clearly marked 1/4 in the center of a mound of stone.

Description of monument and accessories I established to perpetuate the original location of this corner:



I moved the original stone aside and set a 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown on the DIAGRAM, 26" in the ground. I buried the original stone on the north side of the monument.

From Which:

A 5/8" x 30" rebar, set 28" in the ground, with yellow plastic cap marked PLS 848 bears:

- N45°W, 11.5 ft. (no grooves on rebar)
- N45°E, 11.6 ft. (1 groove on rebar)
- S45°E, 13.4 ft. (2 grooves on rebar)
- S45°W, 10.8 ft. (3 grooves on rebar)

Measurements to rebars taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence posts with Property Boundary signs (54-2) 5' east and west of the monument. Set steel guard posts alongside each rebar reference with Bearing Tree (54-3) signs and Land Survey Monument (54-9) signs on each post.



This work was performed by:  
Douglas M. Ferguson PLS 848  
Witnessed by: D. Mitchell Ferguson  
and Rick Saul  
May 5, 1992  
Refer to Grant Co. Survey No.:1217

Office of Surveyor County of Grant  
State of OR I hereby certify that the within instrument was  
filed in this office for record on the 16 day of Oct, 1992  
Robert D. Baggett by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)