CERTIFIED RECORD OF LAND CORNER MONUMENTATION

File #WEG78.N
Index File #A-11 T18S R32E

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 470 dated April 14th, 1883

The government field notes state:

40.00 Set. basalt stone 16x14x10 ins 10 ins in the ground for 1/4 Sec. cor. marked 1/4 on the W. face. dug pits 18x18x12 ins. E & W of stone 5 1/2 ft dist and raised a mound of Earth 1 1/2 ft high. 3 1/2 base alongside.

DIAGRAM
T17S R32E
1/4 33/4
T18S

No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A Stone 16" x 14" x 10" marked 1/4 on East face in mound of stones.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:
20" in ground & erected a mound of stones around it.
I buried the original stone monument face down, top to N, on the S side of the new monument flush with the ground.

U. S. DEPT
OF AGRICULTURE
UNLAWFUL TO DISTURB
T17S R32E
1/4 33/4
T18S
OPLS 1805
1980
CADASTRAL SURVEY
FOREST SERVICE

from which I scribe NEW BEARING TREES:

A 14" DBH PP Bears N12°E 80.5 Ft.,
scribed 1/4S 33 BT
A 12" DBH Juniper Bears S73°W 46.5 Ft.,
scribed 1/4S 4 BT

REGISTERED
PROFESSIONAL
LAND SURVEYOR
F. E. Calkins
OREGON
JULY 13, 1979
F. E. CALKINS
1805

Painted faces & bands around BT's red & attached BT & Attention tags.
Drove a 6 Ft. long steel fence post 1.5 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.
This corner was set August 7, 1980.
Witness: F.R. Palmer, S.E. Trask

Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 8th day of Sept, 1980

Robert M. Bagett by _____
(COUNTY OFFICIAL) (DEPUTY)

FORM R6-7100-57 (9/71)

Z-11