

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


File #WEG78.0  
Index File #A-13 T18S R32E

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 470 dated April 14th, 1883.

The government field notes state:

80.00 Set basalt stone 14x14x10 ins 9 ins in the ground for cor. to Secs. 3, 4, 33 & 34 marked with 3 notches on the E & West edges from which a pine 40 ins diam. bears. N88°E 114 lks dist. marked T17S R32E S.34 B.T. a pine 12 ins diam. bears S68°E 174 lks dist marked T18S R32E.S.3 B.T. No trees within limits in secs. 4 & 33 Dug pits in said secs 18x18x12 ins 5-1/2 ft dist and raised a mound of earth alongside



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A stone 15" x 15" x 9" with 3 notches on E & W faces with a steel fence post on its west face.

From which:

A 39" DBH PP Bears N89-1/2°E 75.4 Ft. Scribed "R" rest grown over  
A 26" DIA. PP Stump 8" High Bears S65°E 114.6 Ft. was cut off below scribing

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked: 24" in ground & erected a mound of stones around it. I buried the original stone monument top down, 3 notches N & S on the S side of the new monument flush with the ground.

U. S. DEPT  
OF AGRICULTURE  
UNLAWFUL TO DISTURB  
T17S R32E  
S33 S34  
S4 S3  
T18S  
OPLS 1805  
1980  
CADASTRAL SURVEY  
FOREST SERVICE

from which I scribe NEW BEARING TREES:

An 8" DBH Juniper Bears N72-1/2°W 108.9 Ft., scribed T17S R32E S 33 BT  
A 15" DBH PP Bears S9-1/2°E 11.7 Ft., scribed T18S R32E S 3 BT  
A 4" DBH Juniper Bears S36°W 24.7 Ft., scribed T18S R32E S 4 BT

Painted faces & bands around BT's red & attached BT & Attention tags.  
Drove a 6 Ft. long steel fence post 1.5 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.  
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.  
This corner was set August 6, 1980  
Witness: F.R. Palmer & S.E. Trask

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*S.E. Calkins*

OREGON  
JULY 13, 1979  
**F. F. CALKINS**  
1980

Office of            County Surveyor            County of            Grant  
State of            Oregon, I hereby certify that the within instrument was filed  
in this office for record on the 8<sup>th</sup> day of Sept, 1980  
*Robert H. B...*  by             
(COUNTY OFFICIAL) (DEPUTY)