CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Original corner established by : Bamford Robb, Deputy Surveyor
under Contract No.366, dated August 18, 1880.

T17S R28E
S34
1/4 ——
S3
T18S
1996
OPLS2734

Surveyor General Record States: Set basalt stone 16x7x6 in mound of stone for 1/4 section corner.

Description of corner evidence found:
Found a stone 12"x9"x6" set in a small mound of stone, marked 1/4 on N. face

See Record Map of Survey No. 1430
Description of monument and accessories set at corner location:
I accept the marked corner stone. At the corner position I set a 2 1/2" x 30" aluminum pipe with attached 2 1/2" aluminum cap, set 20 inches in the ground, surrounded by a mound of stone. I placed the original corner stone west and alongside the aluminum pipe. The cap is stamped as shown in the diagram.

From which I scribe new bearing trees:
A 13" diam. Juniper bears N88°E, 78.00 ft., marked 1/4S34 BT.
A 13" diam. Juniper bears N82°W, 21.04 ft., marked 1/4S34 BT.

From which I set these references:
A 5/8"x30" iron pin, bears North, 10.00 feet, with attached red plastic cap marked CORNERSTONE SURVEYING, INC.
A 5/8"x30" iron pin, bears South, 10.00 feet, with attached red plastic cap marked CORNERSTONE SURVEYING, INC.

I used a steel tape measuring to a 50d nail driven in the side center at root crown of the BT's and magnetic compass, with 20° E. declination. I used a steel tape and magnetic compass, with 20° E. declination, to tie the references.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
SEPTEMBER 19, 1995
JACK L. WATSON
2734
RENEWAL DATE: 6/30/98

Date: October 24, 1996

Office of Surveyor County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 1 day of Nov, 1996
Robert D Beyett by .....
(COUNTY OFFICIAL) (DEPUTY)