CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Original corner established by : Bamford Robb, Deputy Surveyor under Contract No.366, dated August 18, 1880.

Surveyor General Record States: Set stone 16x7x6 in mound of stone for corner to sections 34,35,2, and 3.

T17S R28E
S34 | S35
S3 | S2
T18S
1996
OPLS2734

Description of corner evidence found:
Found 16"x7"x5" stone set in a mound of stone, marked with 6 grooves on the south face, 4 grooves on the west face and 2 notches on the east edge.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
SEPTEMBER 19, 1995
JACK L. WATSON
2734
RENEWAL DATE: 6/30/98

See Record Map of Survey No. 1430
Description of monument and accessories set at corner location:
I accept the marked corner stone . At the corner position I set a 2 1/2" x 30" aluminum pipe with attached 2 1/2" aluminum cap, set 14 inches in the ground, surrounded by a mound of stone. I placed the original corner stone north and alongside the aluminum pipe.The cap is stamped as shown in the diagram.

From which I scribe new bearing trees:
A 6" diam. Juniper bears N27°E, 98.78 ft., marked XBT.
A 12" diam. Juniper bears S73°E, 94.08 ft., marked T18SR28ES2BT
A 18" diam. Juniper bears S55°W, 100.50 ft., marked T18SR28ES3BT.
A 30" diam. Juniper bears N56°W, 55.17 ft., marked T17SR28ES34BT.

I used a steel tape measuring to a 50d nail driven in the side center at root crown of the BT's and magnetic compass, with 20° E. declination.

Date: October 24, 1996

Office of SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 1 day of NOV, 1996
Robert D. Burgett by
(COUNTY OFFICIAL) (DEPUTY)