CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *

The original corner was established in 1880 by Bamford Robb under Contract No. 366 dated August 18, 1880.
The original notes state:

60.00 Pine 24 ins dia.

DIAGRAM

T17S R28E
S36
AP ---
S1
T18S

Description of corner evidence found:

At the assumed location of the called line tree (24" Pine), I found a 24" Pine, down and dead, one hack remaining on the upper side.

Description of monument and accessories I establish to perpetuate the original location of this corner:

At the position of the roothole, set a 2½ x 28" aluminum monument 24" in the ground in a mound of stone.
I establish new bearing trees:
An 8" Juniper bears N28°W, 10.3 ft, scribed APS36BT.
A 9" Juniper bears S13-3/4°W, 29.0 ft, scribed APS1BT.

T17S R28E
S36
AP-----
S1
T18S
PLS1918
1988

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Attention or Land Survey Monument signs. A steel fence post with Attention or Land Survey Monument sign is driven approximately 3-5 feet from the corner.

Smokey Cadastral Survey, Cont. No. 53-04H1-7-4011
Field Book: FB 3-32
Work accomplished: 6/17/88
Witnesses: Tyler Parsons
Louise Parsons
Sharon Parsons
Job No.: 8722G

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Tyler B Parsons
OREGON
JULY 18, 1980
TYLER B. PARSONS
1918

PARSONS SURVEYING
1915 S.E. Stone Street
Corvallis, OR 97333
(503) 752-7515

Office of COUNTY SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 4 day of Nov, 19 88

Robert D Bagott by _____
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

A-214