CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
G.L.O., 1882, by Henry W. Cooke, Contract #427.
Set post with marked stone 12" in ground.
Pits East and West at 5 1/2'.

DIAGRAM

T17S R28E
S 6
1/4
S 7

Description of corner evidence found:

No evidence of original corner found. Set at single proportionate distance between section corners 1/2 mile East and 1/2 mile West.

SEE MAP OF SURVEY #1015.

Description of monument and accessories I established to perpetuate the ~~original~~ location of this corner:

Set 2"X30" alum. pipe with 3" alum. cap, marked as shown, 18" in ground, with mound of stone to cap.
16" Juniper N1°E 70.8' scribed "1/4S6BT".
21" Juniper S84°E 44.4' scribed "1/4S7BT".
Set 6' metal fence post 2.3' East with USFS 54-4 sign.

T17S R28E
S 6
1/4
S 7
1987
PLS 1098

BT's have USFS 54-3 and 54-4 signs, and 60d nail with 1 1/2" alum. disk "C. WAYNE COOK PLS 1098" in side center at base. distance measured to nail. Bearings measured with Silva Ranger compass (Var. 19° East). Corner falls on an East slope +- 350' NW of Dry Soda creek road.

I hereby certify that the above corner was monumented as hereon described on July 15, 1987.
Witnesses: L.R. Edgar, A.D. Cook and S.J. Everett.

REGISTERED PROFESSIONAL LAND SURVEYOR

C. Wayne Cook

OREGON
JULY 22, 1977
C. WAYNE COOK
1098

C. WAYNE COOK
3180 ALDERCREST ROAD
TILLAMOOK, OREGON 97141
503-842-8380

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 17 day of Oct, 19 87
Robert D. Bryant by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

E-3