CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. Z-3

History of original corner establishment:
This corner was originally established by John W. Meldrum under joint contract with David P. Thompson in 1874. Surveyor General Field Notes state:
Set basalt stone 18x16x4 for 1/4 sec corner

DIAGRAM



Description of Corner Evidence Found:
Found a 20"x18"x8" stone partially set with a 1/ (one and slash) visible, the 4 has spalled off. There is also a 5/8" iron pin set alongside with aluminum cap marked MAPS PLS 128 198. Accepted stone as corner location.

Description of monument and accessories I established to perpetuate the original location of this corner:
At position of original stone,
Set 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown in DIAGRAM, 20" in the ground. Placed pin inside monument pipe. Set the original stone North alongside pipe and raised a mound of earth and stone around pipe.

From which:

A Juniper 8" dia. bears N62°W, 70.5 ft., scribed: 1/4 S31 BT.
A Ponderosa Pine 28" dia. bears N55°E, 266.6 ft. scribed: 1/4 S31 BT.
A Ponderosa Pine 6" dia. bears S71°E, 158.5 ft., scribed: 1/4 S6 BT.
A Juniper 8" dia. bears N77°W, 7.4 ft., scribed; 1/4 S6 BT.

Measurements to accessories taken with a magnetic compass, declination 17°east, and a nylon clad steel tape. Set steel fence post with Land Survey Monument sign 5'north. Nailed a brass washer stamped PLS 848 on blaze above BT scribe as taken this survey. Nailed Bearing Tree signs above blaze and Land Survey Monument signs on back of each tree as required. Painted a 6" red band above Bearing Tree signs and painted blaze red.

Renewal Date:
12/31/98

This work was performed by:
Douglas M. Ferguson, PLS 848
Witnessed by: D. Mitchell Ferguson and Brad Cates
Date: 11- 3-95
Refer to Grant County Map of Survey No. 1462

Office of Surveyor County of Grant
State of OR I hereby certify that the within instrument was filed in this office for record on the 2 day of Feb, 19 98
Robert D Bagett by
(COUNTY OFFICIAL) (DEPUTY)