CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. Z-14

History of original corner establishment:
This corner was originally established by John W. Meldrum under joint contract with David P. Thompson in 1874, under GLO Contract Number 220. Surveyor General Notes State:
Set basalt stone 18x10x10 for 1/16 sec cor.

DIAGRAM



Description of Corner Evidence Found:

Found original stone 18"x12"x10" with "1/16" marked on the north face, set at the base of a steep east slope.

Description of monument and accessories I established to perpetuate the original location of this corner:
At the position of the original stone,
Set 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown in DIAGRAM, 24" in the ground, set original stone north alongside pipe, and built a ring of stone around the pipe.

From which:

A Juniper 12" in dia., bears N2°E, 135.0 ft., scribed: W 1/16 S34 BT.
A Juniper 16" in dia., bears S6°E, 72.3 ft., scribed: W 1/16 S3 BT.

Measurements to accessories taken with a magnetic compass, declination 17°east, and a nylon clad steel tape. Set steel fence post with Land Survey Monument sign 5'north. Nailed a brass washer stamped PLS 848 on blaze above BT scribe as taken this survey. Nailed Bearing Tree signs above blaze and Land Survey Monument signs on back of each tree as required. Painted a 6" red band above Bearing Tree signs and painted blaze red.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848

Renewal date:
12/31/98

This work was performed by:
Douglas M. Ferguson, PLS 848
Witnessed by: D. Mitchell Ferguson and Brad Cates
Date: 10-10-95
Refer to Grant County Map of Survey No. 1462

Office of Surveyor County of Grant
State of OR I hereby certify that the within instrument was filed in this office for record on the 2 day of Feb, 1998
Robert D. Baggett by
(COUNTY OFFICIAL) (DEPUTY)

Z-14