

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by G. Thurston
in 1873 under contract #191.
Set granite stone 20x16x8.

DIAGRAM

T18S
R26E R27E
S13	S18
S24|S19

Description of corner evidence found:

Found 20x16x8 stone with 3 notches on the south face.

Description of monument and accessories | established to perpetuate the
original location of this corner:

At the position of the found original stone I set a 2 1/2" x 30"
aluminum pipe with 3 1/4" aluminum cap 8" in the ground in a mound
of stone,
stamped as shown:

T18S
R26E R27E
S13	S18
S24|S19
1986
RLS 1664

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Carl E. Sundet

OREGON
JULY 14, 1978
CARL E. SUNDET
1664

From Which:

A 5" Juniper bears N 71° W a distance of 84.6 feet,
scribed XBT.

A 9" Juniper bears N 71° E a distance of 170.4 feet,
scribed XBT.

A 17" Ponderosa Pine bears S 49° E a distance of 84.4 feet,
scribed T18SR27ES19BT.

A 16" Ponderosa Pine bears S 07 1/2° W a distance of 119.5 feet,
scribed T18SR26ES24BT.

See also Record Map of Survey #969.

Compass Declination 19° E.

All bearing trees have a brass tag marked RLS 1664 in the bottom of
the blaze and Forest Service Bearing Tree and 54-9 signs.

I hereby certify the above corner was perpetuated as herein
described on October 24, 1986.

Witness: G. Grisell

D. Morrill

Office of..... *Surveyor* County of..... *Grant*

State of..... *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)