

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by G. Thurston
in 1873 under contract #191.
Set sand stone 16x10x6.

DIAGRAM

T18S
R26E R27E
1/4
S241S19

Description of corner evidence found:

Found no evidence on original 16x10x6 stone.

Description of monument and accessories I established to perpetuate the
original location of this corner:

At the position established by proportional measurement I set a
2 1/2" x 30" aluminum pipe with 3 1/4" aluminum cap 24" in ground
in mound of stone, stamped as shown:

T18S
R26E R27E
1/4
S241S19
1986
RLS 1664

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 14, 1978
CARL E. SUNDET
1664

From Which:

A 4" Juniper bears N 09° W a distance of 115.5 feet,
scribed 1/4S24BT

An 8" Mountain Mahogany bears N 84 1/2° E a distance of 145.0 feet,
scribed 1/4S19BT

See also Record Map of Survey #969.

Compass Declination 19° E.

All bearing trees have a brass tag marked RLS 1664 in the bottom
of the blaze and Forest Service Bearing Tree and 54-9 signs.

I hereby certify the above corner was perpetuated as herein
described on October 23, 1986

Witness: D. Morrill

Office of... G. Grisel *Surveyor* County of... *Grant*
State of... *OR* I hereby certify that the within instrument was filed in this office
for record on the... *16* day of... *JAN*... 19... *87*
... *Robert A. Sargent* by...
(COUNTY OFFICIAL) (DEPUTY)