

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by A. Gesner.
in 1874 under contract #206.
Set stone 16x14x6.

DIAGRAM

T18S R26E
S23	S24
S26|S25

Description of corner evidence found:

Found 16x14x6 basalt stone with one notch east and two possible notches south in a mound of stone.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the found original stone I set a 2 1/2" x 30" aluminum pipe with 3 1/2" aluminum cap 6" in the ground in a mound of stone,
stamped as shown:

T18S R26E
S23	S24
S26|S25
1986
RLS 1664

From which:

- A 20" Ponderosa Pine bears N 61 1/2° E a distance of 15.4 feet, scribed T18SR26ES24BT.
- A 9" Ponderosa Pine bears S 70 1/2° E a distance of 49.4 feet, scribed T18SR26ES25BT.
- A 16" Ponderosa Pine bears N 03 1/2° W a distance of 39.0 feet, scribed T18SR26ES23BT.
- A 17" Ponderosa Pine bears S 35 1/2° W a distance of 36.1 feet, scribed T18SR26ES26BT.

See also Record Map of Survey #969.

Compass Declination 19° E.

All bearing trees have a brass tag marked RLS 1664 in the bottom of the blaze and Forest Service Bearing Tree and 54-9 signs.

I hereby certify the above corner was perpetuated as herein described on November 5, 1986.

Witness: G. Grisel

P. Goehring

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 16 day of January, 1986
Robert D. Leggett by _____
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 14, 1978
CARL E. SUNDET
1664