

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by A. Gesner.
in 1874 under contract #206.
Set stone 12x8x6.

DIAGRAM

T18S R26E
1/4
S261S25

Description of corner evidence found:

Found no evidence on original 12x8x6 stone.

Description of monument and accessories I established to perpetuate the

original location of this corner:

At the position established by proportional measurement I set a
2 1/2" x 30" aluminum pipe with 3 1/4" aluminum cap 26" in ground
in mound of stone, stamped as shown:

T18S R26E
1/4
S261S25
1986
RLS 1664

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 14, 1978
CARL E. SUNDET
1664

From Which:

A 9" Ponderosa Pine bears S 39° E a distance of 23.8 feet,
scribed 1/4S25BT.

An 8" Ponderosa Pine bears S 41° W a distance of 59.6 feet,
scribed 1/4S26BT.

See also Record Map of Survey #969.

Compass Declination 19° E.

All bearing trees have a brass tag marked RLS 1664 in the bottom
of the blaze and Forest Service Bearing Tree and 54-9 signs.

I hereby certify the above corner was perpetuated as herein
described on November 5, 1986

Witness: P. Goehring
G. Grisel

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*16*..... day of.....*Sept*....., 19.....*87*.....
.....*Robert J. D. [Signature]*..... by.....
(COUNTY OFFICIAL) (DEPUTY)