

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: NO HISTORY TO THE LOCATION OF THIS CORNER.

DIAGRAM
T. 18 S., R. 26
E., W.M.

CW^{1/16} - S33

Description of corner evidence found: NONE

Description of monument and accessories I established to perpetuate the original location of this corner

SINCE THERE WAS NO EVIDENCE OF A CORNER SET I USED A SINGLE PROPORTION TO SET THIS CORNER MIDWAY BETWEEN THE WEST 1/4 CORNER AND CENTER 1/4 CORNER OF SECTION 33. I SET A 2" X 36" GALVANIZED IRON PIPE 26" IN THE GROUND, WITH A ROCK MOUND AND A 2 1/2" BRASS CAP MARKED:

NEW BEARING TREES:

A WHITE FIR, 9" IN DIAMETER, BEARS NORTH 11° EAST, 39.3 FEET;
A WHITE FIR, 12" IN DIAMETER, BEARS NORTH 81° EAST, 26.3 FEET.

T18S
R26E
C W^{1/16} C
S33
LS 540
1973

REGISTERED
PROFESSIONAL
LAND SURVEYOR

George J. Cook
OREGON
JULY 1, 1961
GEORGE J. COOK
540

I HEREBY CERTIFY THE ABOVE CORNER MONUMENT WAS RE-ESTABLISHED AS HEREIN DESCRIBED ON SEPT. 8, 1973.

WITNESSES:

s/ *John C. Blunt*
s/ *Jack L. Smith*

Office of *County Surveyor* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office for record on the *5th* day of *November*, 19*73*, at *11:26* o'clock *a.m.*, (signed)
Robert D. Smith by _____
(COUNTY OFFICIAL) (DEPUTY)