


CORNER RESTORATION

CORNER: NE Cor. Sec. 8 Twp. 18 S. Range 28 E., W.M.

ORIGINAL SURVEY BY: Henry W. Cooke

CONTRACT NUMBER: 494

CONTRACT DATE: January 16, 1884



Subsequent surveys:

- Nathan C. Erickson, Cadastral Surveyor, under special instructions approved June 3, 2010, Group No. 2334.
Completed June 30, 2010

ORIGINAL DESCRIPTION: *Set a basalt stone 14x14x10x ins 10 ins in ground for cor to secs 4, 5, 8 & 9 marked with 5 notches on S. and 4 notches on E. edges and raised a mound of stone 2 ft high 4½ ft base alongside.*

► 2011:

The cor. of secs. 4, 5, 8, and 9, determined at the center of the original mound of stone.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd

T 18 S	R 28 E
S 5	S 4
S 8	S 9
2010	

from which

A juniper, 20 ins. diam., bears N 48° E., 185.8 ft. dist., mkd.
T18S R28E S4 BT.

A twin juniper, 23 ins. diam., bears S. 72 1/4° E , 165.1 ft. dist., mkd.
T18S R28E S9 BT on the northerly trunk.

A juniper, 16 ins. diam., bears N. 56 1/4° W., 58.3 ft. dist., mkd.
T18S R28E S5 BT.

No other accessories available.

RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS
Grant County Surveyor

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

AUG 22 2011

BY:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2012

August 19, 2010

EVIDENCE FOUND: None. No field visit was made for this Corner Restoration Report, it is prepared from record information. See Record Map of Survey No. 1932 filed in the office of the Grant County Surveyor.