


CORNER RESTORATION

CORNER: S1/4 Cor. Sec. 8 Twp. 18 S. Range 28 E., W.M.

ORIGINAL SURVEY BY: Henry W. Cooke

CONTRACT NUMBER: 494

CONTRACT DATE: January 16, 1884



Subsequent surveys:

- ▶ Nathan C. Erickson, Cadastral Surveyor, under special instructions approved June 3, 2010, Group No. 2334.
Completed June 30, 2010

ORIGINAL DESCRIPTION: *Set a basalt stone 16x14x10x ins 11 ins in ground for 1/4 sec cor marked 1/4 on north face. dug pits 18x18x12 ins E & W of cor 5 1/2 ft. dist and raised a mound of earth 1 1/2 ft. high 3 ft. base alongside.*

- ▶ 2011: The 1/4 cor. of secs. 8 and 17, monumented with the original basalt stone, 16x 14 x 10 ins., firmly set, projecting 8 ins. above the ground, with collar of 3 stones, mkd. with illegible chisel marks.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 18 S R 28 E
S 8
1/4 ———
S 17
2010

Raised mound of stone, 3 ft. base, 20 ins. high, 5 ft. S. of cor.


Bury original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.


RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS
Grant County Surveyor

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

AUG 22 2011

BY: 



EXPIRES: 6/30/2012

August 19, 2010

EVIDENCE FOUND: None. No field visit was made for this Corner Restoration Report, it is prepared from record information. See Record Map of Survey No. 1932 filed in the office of the Grant County Surveyor.