

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. R-25

History of original corner establishment:

Corner was originally established under G. L. O. contract No. 191, by George H. Thurston, during July, 1873. Surveyor General's notes state: "Set stone 18 X 12 X 4 for cor. to secs. 24, 25, 19 and 30. From which: A Pine 28 ins. dia. bears N80°W, 55 lks."

DIAGRAM

	T18S	
R27E		R28E
S24		S19
	+	
S25		S30

Description of corner evidence found:

Found no trace of record stone. Area has been logged. Found 5' Pine stump, 44" in diameter, scribed "8S S24." Measured S80°E, 36.3 ft.

Description of monument and accessories established to perpetuate the original location of this corner:

At measured point, set 2 1/2" X 30" aluminum pipe and cap marked:
Set pipe 20" in the ground and mound of stone around to cap.
From which by magnetic declination of N20°E:
A 14" Fir bears N72°E, 139.2 ft. scribed T18S R28E S19 BT.
An 11" Fir bears S23°E, 50.9 ft. scribed T18S R28E S30 BT.
A 20" Fir bears S18°W, 59.7 ft. scribed T18S R27E S25 BT. A 12" Pine bears N25°W, 49.5 ft. scribed T18S R27E S24 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on the BTs. Placed 54-2 and 54-4 on a steel fence post 5' east and 54-2 on a steel fence post 10' west of the corner. Corner falls in bog area.

	T18S	
R27E		R28E
S24		S19
	+	
S25		S30
OR PLS 1051		
1982		

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel T. Rowland
Larry D. Shirley

July 29, 1982

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour
**OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051**

Office of.....County Surveyor.....County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the...28... day of...Oct... , 19...82
.....*Robert D. Begett*..... by
(COUNTY OFFICIAL) (DEPUTY)

R-25
R-1