

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

DIAGRAM

T18S R28E

S27

S34

History of original corner establishment:

The original corner was set by Deputy Surveyor Henry Cooke in 1884 under GLO Contract #494 dated January 16, 1884 and approved August 2, 1884.

39.96 Set basalt stone 18X16X10 for the $\frac{1}{4}$ corner to sections 27 & 34 with $\frac{1}{4}$ on the north face and raised mound of stone alongside.

Description of corner evidence found:

At the location of the corner found a stone 18X15X11 with "1 /" visible and discernable marks were the "4" should be but they were not legible. There was a mound of 4 stones alongside.

Description of monument and accessories I establish to perpetuate the original location of this corner:

Set a 2½" X 30" aluminum pipe with a 3½" aluminum cap set 16" in the ground in a mound of stone. I buried the corner stone west and alongside the pipe.

From which: A 4" Juniper bears S58°55'49"E 32.29' scribed "X BT".

A 5" Juniper bears N82°18'44"E 72.08' scribed "X BT".

A 4" double bole Juniper bears N36°52'41"E 127.68' scribed "X BT".

A 4" Juniper bears S67°25'44"W 37.86' scribed "X BT".

Distances were shot to a 16d aluminum nail driven perpendicular to the monument at the center of the tree near the root crown. Bearings were from a local grid and turned with a Wild TCR703 to the center of the BT face.

8/24/04

Witness: Kyle Myers

RENEWAL 6/30/06

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JUL 20, 1993
CARL J. STOUT
#2632

Office of County Surveyor, County of Grant, State of Oregon,
I hereby certify that the within instrument was filed in this office
for record on the 28 day of SEPT, 2004.

Robert D. Bryant
(COUNTY OFFICIAL)

by

(DEPUTY)