


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The original GLO survey was done by Bamford Robb under contract no. 366, dated August 18, 1880.



Description of corner evidence found:



This corner was not set under the original GLO survey. Nothing found.

Description of monument and accessories I established to perpetuate the original location of this corner:

On 11/10/86 at the proportioned location we set an all alum. monument, 2½" dia. x 30" long, with a 3" dia. cap stamped " W 1/16, S 18, T 18 S, R 29 E, WM, PLS 1288, 1986", buried 20", 10" above the ground. Set a steel fence post 1' north with a land survey sign attached.

A 8" w juniper bears N 71°10'E, 28.8 feet, scribed "W 1/16, C-C, S 18, BT"
A 6" w juniper bears S 15°30'E, 14.3 feet, scribed "W 1/16, C-C, S 18, BT"

Both BT's have a 6" band of red paint, BT and LS signs and a brass washer stamped "PLS 1288" set at the base.



GRANT COUNTY
SURVEY # 968

Office of SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 6 day of April, 1987
Chris T. Palmer by _____
(COUNTY OFFICIAL) (DEPUTY)