

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. L-13

History of original corner establishment:

Corner was originally established by Bamford Robb, in Aug. 1880. under General Land Office Contract No. 366. The U.S. Surveyor Generals Notes State: Set Stone 14x12x6 in mound of Stone for 1/4 Sec. Cor.

from which:

A pine 8 " dia., Bears N 5°W., 31 lks dist.

DIAGRAM

T18S R29E
1/4
S161S15
1987
RLS 848

Description of corner evidence found:

Found 16"x12"x12" stone with 1/4 on face, set in a mound of stone.

From Which:

Found 38" Pine, dead and down scribed: 1/4 S BT. Tree looks like it has slid downslope a few feet. Bears N10°E., 25.6 ft. (Record N 5°W., 20.5 ft.) Accepted the above described stone as the corner.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 12" in the ground, set the original stone North alongside pipe and raised a mound of stone and earth around pipe.

From Which:

A Fir 6" dia., Bears N67°E., 22.8 ft., scribed: 1/4 S15 BT
A Pine 6" dia., Bears S55°E., 19.6 ft., scribed: 1/4 S16 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North & South 4 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1909
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: June 9, 1987
Refer to Map of Survey No. 1005

Office of Sumner County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 2 day of Oct, 1987
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)