


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by James P. Currin under
General Land Office Contract No. 348 dated
January 22, 1880.

Surveyor General's records state:

N89°50'E on true N bdy sec 6
22.75 Creek 10 lks wide head of S. Fork John Days
River
39.25 Set basalt stone 14X10X6 in stone mound
for 1/4 sec cor.



F.B. 3 P.19 & 20
A-3

Description of corner evidence found:

At assumed corner location found basalt stone 19"X10"X6" lying flat
marked " $\frac{1}{4}$ " on down face, stone lying in center of loose stone mound
3 foot diameter consisting of approximately 7 stones. Corner stone
did not appear disturbed and is accepted as original corner location.

Description of monument and accessories established to perpetuate the
original location of this corner:

At position of original stone in stone mound, set
2 1/2 inch 30 inch long aluminum pipe 16 inches in
ground to bedrock with 3 1/4 inch aluminum cap
marked as shown:

Marked new bearing trees:


a 17" Ponderosa Pine bears North 14°00' West, 26.7 ft.,
scribed-1/4S31BT;
an 11" Juniper bears South 58° West, 23.5 ft.,
scribed-1/4S6BT.

Deposited original stone North of cap and raised 3 foot
diameter stone mound to cap. Set steel post 5 feet East
with sign 54-4 facing corner.


Painted red band and faces red and nailed signs 54-3 and
54-4 to new bearing trees. Nailed brass washer stamped-
AS&E LS1026-to blaze of new bearing trees.

I hereby certify the above corner monument was re-established
as herein described on June 20, 1984.


Witnesses: David B. Armstrong
William Robinson



M.V. 18°30'E.



David B. Armstrong



Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 10 day of JAN, 1985
Robert D. Dapitt by _____
(COUNTY OFFICIAL) (DEPUTY)