

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by S.W. Lachland, under General Land Office Contract No. 384.

Surveyor General's records state:

Set a basalt stone 14x8x5 ins., in mound of stone for $\frac{1}{4}$ sec. cor. from which,

A pine, 28 in. dia. bears N20°W 21 lks. dist.

Note: No restoration appears in County records.

Description of corner evidence found:

At assumed corner location, I found 18x8x7 in. stone, above ground in a mound of stone, no markings found from which;

A p.pine, 30 in. dia. bears N20°W, 21 lks. dist., scribing visible

A p.pine, 10 in. dia. bears S88°E, 30 ft. with old location poster

Description of monument and accessories I established to perpetuate the original location of this corner:

As the evidence in vicinity of corner agrees with GLO original record, I set at the location of the mound of stone a 30 in. long 2 in. dia. alum. pipe in ground, in a mound of stone, with 3 in. alum. cap marked:

	R31E	
	$\frac{1}{4}$	
T17S		S32
T18S		S5
1978		
PLS 1067		


New Bearing Trees:

A mahogany, 4 in. dia. bears S42°E, 16.6 ft. dist. scribed $\frac{1}{4}$ S5 BT


A p.pine, 22 in. dia. bears N35°W, 15.0 ft. dist. scribed $\frac{1}{4}$ S32 BT

I placed USFS signs and a brass washer marked PLS 1067 on all bearing trees and buried the 18x8x7 in. stone alongside the alum. pipe. I hereby certify the above corner monument was re-established as herein described on June 9, 1978.

Witnesses: Johnny D. Smith
Darryl J. Anderson
Assistants



Sherman E Anderson



Office of *Surveyor* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the *21* day of *Sept*, 1978.
Robert D. Engle by _____
(COUNTY OFFICIAL) (DEPUTY)