

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by S.W. Lachland, under General Land Office Contract No. 384.

Surveyor General's records state:

Set basalt stone 14x8x5 ins. in mound of stone for corner to sections 4,5,32 & 33 from which,

A pine, 36 in. dia. bears N46°E, 149 lks. dist. marked T17S, R31E S33 BT

A pine, 32 in. dia. bears S72°W, 108 lks. dist. marked T18, R31E S5 BT

Note: No restoration appears in County records.

Description of corner evidence found:

At the assumed corner location, I found a mound of stone in a fence line, from which

A p.pine, 38 in. dia., with open scribed face, bears N46°E, 149 lks. dist.

A p.pine, 34 in. dia., with open scribed face, bears S72°W, 108 lks. dist.

Description of monument and accessories I established to perpetuate the original location of this corner:

As evidence in vicinity of corner agrees with GLO original record, at location of the found mound of stone, I set a 30 in. long 2 in. dia. alum. pipe in ground, in mound of stone, with a 3 in. alum. cap marked:

		R31E
T17S	S32	S33
T18S	S5	S4
	1978	

New Bearing Trees:

PLS 1067


A mahogany, 6 in. dia. bears S29°30'E, 26.5 ft. dist., scribed S4 T18S R31E BT

A mahogany, 6 in. dia. bears N45°30'W, 40.0 ft. dist., scribed S32 T17S R31E BT


I placed a brass washer marked PLS 1067 and USFS signs on all bearing trees. I hereby certify the above corner monument was re-established as herein described on June 9,

1978. Witnesses: Johnny D. Smith

Darryl J. Anderson
Assistants



Sherman E. Anderson



Office of *Surveyor* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the *21* day of *Sept*, 19*78*
Robert D. Smith by _____
(COUNTY OFFICIAL) (DEPUTY)