

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1883 by Reuben R. Leigh, under General Land Office Contract No. 462.

Surveyor General's records state:

Set a post 3 ft. long 3 in. square 24 in. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N face from which,

A pine, 48 in. dia. bears N30°E 133 lks. dist., marked $\frac{1}{4}$ S BT
A pine, 18 in. dia. bears S10°E 95 lks. dist., marked $\frac{1}{4}$ S BT

DIAGRAM

T18S	R31E
$\frac{S5}{S8}$	$\frac{1}{4}$

Description of corner evidence found:

At the assumed corner location, I found two bearing trees;

A p.pine, 48 in. dia., bears N30°E, 133 lks. dist., scribing partially visible
A p.pine, 18 in. dia., bears S10°E, 95 lks. dist., faced grown over

Description of monument and accessories I established to perpetuate the original location of this corner:

As evidence in vicinity of corner agrees with GLO original record, at the location of record bearing and distances from the bearing trees, I set a 30 in. long 2 in. dia. galv. iron pipe in ground, in a mound of stone and earth, with a 2 in. brass cap marked:

T18S	R31E
$\frac{1}{4}$	$\frac{S5}{S8}$
1978	
PLS 1067	

I placed a 54-5 + 54-4 USFS signs and a brass washer marked PLS 1067, on a pine 10 in. dia. N14°E, 37 lks. dist. I placed USFS signs and a brass washer marked PLS 1067 on all bearing trees. I hereby certify the above corner monument was re-established as herein described on June 9, 1978. Witnesses: Johnny D. Smith
Darryl J. Anderson
Assistants

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Sherman E. Anderson

OREGON
JULY 30, 1976
SHERMAN E. ANDERSON
1067

Office of *Surveyor* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the *21* day of *Sept*, 19*78*
Robert D. Baggett by
(COUNTY OFFICIAL) (DEPUTY)