


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Line tree established by Reuben R. Leigh under
General Land Office Contract No. 462 dated
April 11, 1883.

Surveyor General's records state:
North bet secs 21 & 22 va 19°E
24.60 Pine 60 ins dia
24.80 Canyon 75 ft deep course East



Description of corner evidence found:

At assumed line tree location found a 54" diameter Ponderosa Pine
sawed stump 48 inches high with 2 distinct healed hack marks on
North face, area of South hacks removed with log. Accept as original
line tree. Bottom of ravine 20 lks (13.2 ft.) North as per record.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Accept found stump as original line tree and perpetuated location.
Magnetic Declination 19° East.

Marked 2 bearing trees:

a 10" dbh Ponderosa Pine bears South 30° West, 35.5 ft.,
scribed "APS21BT";
a 9" dbh Ponderosa Pine bears South 60° East, 17.9 ft.,
scribed "APS22BT".

Nailed brass washer marked "AS&E LS 1026" in lower blaze of BT's.

Painted 6 inch red band and faces red and nailed signs 54-3 and 54-4
on bearing trees. Also painted 6 inch red band on line tree stump
and nailed sign 54-4 to South face and sign 54-2 to East face. Set
steel post with signs 54-2 and 54-4 North, 6.0 ft. from line tree
stump.

I hereby certify the above line tree was re-established as herein
described on September 26, 1983.

Office of Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 28 day of Dec, 1983
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David B. Armstrong

10/28/83 OREGON
AUGUST 22, 1975
DAVID B. ARMSTRONG
1026