

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1883 by Reuben R. Leigh, under General Land Office Contract No. 462.

Surveyor General's records state;

Set a basalt stone 16x14x5 ins., 11 ins. in ground for $\frac{1}{4}$ sec. cor to sections 20 & 29 from which;

A pine, 36 in. dia. bears N73°W, 20 lks. dist. marked $\frac{1}{4}$ S BT

A mahogany, 10 in. dia. bears S22°E, 38 lks. dist. marked $\frac{1}{4}$ S BT

Note: No restoration appears in County records.

Description of corner evidence found:

At assumed corner location, I found 16x14x5 stone, 8 in. above ground, marked $\frac{1}{4}$ on north face, from which

A dead and down mahogany, scribed, bears S22°E, 38 lks. dist.

A dead and down pine, scribed, bears N70°W, 20 lks. dist.

Description of monument and accessories I established to perpetuate the original location of this corner:

As evidence in vicinity of corner agrees with GLO original record, at the location of the found 16x14x5 in. stone, I set a 30 in. long 2 in. dia., galv. iron pipe in ground, in a mound of stones, with a 2 in. brass cap marked:

T18S R31E
 $\frac{1}{4}$ $\frac{S20}{S29}$
1978
PLS 1067

New Bearing Trees:

A juniper, 6 in. dia., bears S33°15'W, 4.4 ft. scribed $\frac{1}{4}$ S29 BT

A juniper, 6 in. dia., bears N15°30'W, 19.2 ft. dist. scribed $\frac{1}{4}$ S20 BT

I buried the 16x14x5 in. stone alongside the iron pipe, placed brass washers marked PLS 1067 below the scribing, and placed USFS signs on all new bearing trees. I hereby certify the above corner monument was re-established as herein described on May 31, 1978. Witness: Johnny D. Smith

Assistant

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Sherman E. Anderson

OREGON
JULY 30, 1976
SHERMAN E. ANDERSON
Office of

Surveyor County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the *21* day of *Sept*, 19*78*
Robert D. Seifert by
(COUNTY OFFICIAL) (DEPUTY)