


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

R-9

History of original corner establishment:

The original GLO survey was done by Reuben R. Leigh under contract no. 462, dated April 11, 1883.



The field notes state:

North, 80.00 chs, set a basalt stone 14 x 14 x 12 ins. for corner to Sections 20, 21, 28 and 29 with 2 notches on the S and 4 notches on the E edges from which bears a pine 12 in. dia. N 42°E, 28 lks, marked "T 18 S, R 31 E, S 21, BT", a mahogany 8 in. dia. S 05°E, 8 lks, marked T 18 S, R 31 E, S 28, BT", a pine 20 in. dia. S 18°W, 55 lks, marked T 18 S, R 31 E, S 29, BT", a pine 10 in. dia. N 38°W, 46 lks, marked T 18 S, R 31 E, S 20, BT".

Description of corner evidence found:

The original stone was not found. The corner was set from the BT's in Sections 20, 21 and 29.

A 18 in. dia. pine bears N 38°W, 30.0'
A 18 in. dia. pine stump bears N 42°E, 58.4'
A 30 in. dia. pine bears S 18°00'W, 36.2'

All BT's have visible scribing.



Description of monument and accessories I established to perpetuate the original location of this corner

On 4/29/87, at the location determined from the BT's, we set an all alum. monument, 2½" x 30", with a ¾" dia. cap stamped "S 20, S 21, S 28, S 29, T 18 S, R 31 E, 1987, PLS 1288", buried 20", 10" above the ground in a stone mound. Attached a land survey and a boundary sign to a steel fence post 2' north of the corner.

A 9 in. dia. w. fir bears S 51°50'E, 14.6', scribed "S 28, T 18 S, R 31 E, BT"

A 7 in. dia. w. fir bears N 44°36'E, 24.7', scribed "S 21, T 18 S, R 31 E, BT" These have a 6" band of red paint, Attention and BT sign

All BT's have a 6" band of red paint, Attention and BT signs.



Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 18 day of June, 1987, at o'clock m., (signed)
Robert R. Baggett by
(COUNTY OFFICIAL) (DEPUTY)

R-9