

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


X-9

History of original corner establishment:

The original GLO survey was done by Rueben R. Leigh under contract no. 462, dated April 11, 1883.

The field notes state:

North, 40.00 chs, set a 24 x 14 x 3 ins. stone for $\frac{1}{4}$ sec. Cor. from which bears a 30" in. dia. pine, S 26°E, 43 lks, a 30 in. dia. pine, S 12°W, 32 lks, Both BT's marked " $\frac{1}{4}$ S, BT".



Description of corner evidence found:

Found a 22 x 12 x 5 ins. stone marked with a " $\frac{1}{4}$ " on the west face from which bears:

A 24 in. dia. pine, S 09°34'E, 22.0'
A 28 in. dia. down pine snag, S 23°45'W, 28.8'



Both BT's have visible scribing.

Description of monument and accessories established to perpetuate the original location of this corner

On 4/22/87, at the location of the stone, we set an all alum. monument, 2 $\frac{1}{2}$ " x 30", with a 3 $\frac{1}{4}$ " dia. cap stamped " $\frac{1}{4}$, S 32, S 33, T 18 S, R 31 E, 1987, PLS 1288", buried 22", 8" above the ground in a stone mound. Set a steel fence post 2' north with boundary and land survey signs attached.

A 14 in. w. fir bears N 67°14'W, 9.1', scribed " $\frac{1}{4}$, S 32, BT".

All BT's have a 6" band of red paint, Attention and BT signs.



Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 18 day of June, 1987, at o'clock m., (signed)
Robert D. Bager by
(COUNTY OFFICIAL) (DEPUTY)

X-9