

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


2-9

History of original corner establishment:

The original GLO survey was done by Reuben R. Leigh under contract no. 462, dated April 11, 1883.

The field notes state:

East, 80.00 chs, set a basalt stone 18 x 16 x 10 ins. for corner to Sections 4, 5, 32, and 33, from which a 40 in. dia. pine bears N 60°E, 173 lks, marked "T 18 S, R 31 E, S 33, BT", a 20 in. dia. pine bears S 10°E, 42 lks, marked "T 19 S, R 31 E, S 4, BT" a pine 24 in. dia. bears S 38°W, 38 lks, marked "T 19 S, R 31 E, S 5, BT", a mahogany 14 in. dia. bears N 74°W, 34 lks, marked "T 18 S, R 31 E, S 32 BT"



Description of corner evidence found:

Found 18 x 16 x 8 ins. stone from which bears:


- A 40 in. dia. pine stump, N 60°E, 120'±
- A 30 in. dia. pine, S 07°55'E, 29.2'
- A 30 in. dia. pine, S 37°23'W, 33.6'
- A 12 in. dia. mahogany snag, N 72°W, 25.0'

All BT's have visible scribing.

Description of monument and accessories I established to perpetuate the original location of this corner

On 5/18/87, at the location of the stone, we set an all alum. monument, 2½"x 30", with a ¾" dia. cap stamped "S 4, S 32, S 33, T 18 S, T 19 S, R 31 E, 1987, PLS 1288", buried 24", 6" above the ground in a stone mound. Attached a boundary sign and land survey sign to a steel fence post 2' north of the corner.

- A 7 in. dia. w. fir bears N 24°25'W, 5.0', scribed "S 32, T 18 S, R 31 E, BT"
 - A 14 in. dia. w. fir bears N 56°00'E, 29.6', scribed "S 33, T 18 S, R 31 E, BT"
- All BT's have a 6 in. band of red paint, Attention and BT signs.



Office of Surveyor County of Grant & Harney
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 18th day of June, 1987, at o'clock m., (signed)
Chris T. Palmer by (DEPUTY)
COUNTY OFFICIAL

Robert D. Lutz
G.C.S.

2-9