

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

File #WEG78.R  
Index File

History of original corner establishment:

Original corner set by Reuben R. Leigh  
under Contract Number 489 August 15, 1883.  
dated August 15, 1883

DIAGRAM  
T18S R32E  
  
1/4  $\frac{S\ 3}{S10}$

The government field notes state:

39.92 Set a basalt stone 14x9x8 ins 9 ins  
in the ground for 1/4 sec. cor. marked 1/4  
on north face from which a pine 4 ins. diam. bears  
N 35° E. 66 lks dist. marked 1/4 S B.T. A pine 20 ins.  
diam. bears S 5° E. 48 lks dist. marked 1/4 S B.T.

No record of subsequent remonumentation found in county records.

Description of corner evidence found:

I did not find the original stone monument. I reestablished the corner  
measuring from the face of the two original bearing trees at which point I found  
a mound of small stones and a steel fence post 3 ft. long with 8" above ground.  
From the corner position to the face of the BT's.

A 31" DBH PP Bears S3 1/2° E 31.7 Ft. Scribed "4S" rest grown over.  
A 10" Dia. PP stump Bears N45° E 43.6 Ft. No Scribing visible

as only 3" of the very bottom of the scar was left when the tree  
was cut. The cut off post was set by a BLM employee as part of  
an unrecorded administrative survey. BLM corner report card  
is attached.

Description of monument and accessories I established to perpetuate  
the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with  
3-1/4" cap marked:  
20" in ground & erected a mound of stones around  
it.

U.S. DEPT.  
OF AGRICULTURE  
UNLAWFUL TO DISTURB  
T18S R32E

from which I scribe NEW BEARING TREES:

A 16" DBH PP Bears S55° E 33.7 Ft., scribed 1/4 S10 BT  
An 11" DBH PP Bears N81° E 24.8 Ft., scribed 1/4 S 3 BT 1/4  $\frac{S\ 3}{S10}$

OPLS 1805  
1980  
CADASTRAL SURVEY  
FOREST SERVICE

Painted faces & bands around BT's red & attached BT & Attention tags  
& nailed a brass washer to the new BT blaze marked PLS 1805.  
Drove a 6 Ft. long steel fence post 2.2 Ft. in ground 5.7 Ft. N of corner &  
attached an attention tag to it.  
Used steel tape & magnetic staff compass with 20° East variation, measuring  
to the center of the new BT's.  
This corner was set August 6, 1980.  
Witness: F.R. Palmer & S.E. Trask

Office of County Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed  
in this office for record on the 16 day of Sept, 1980  
Robert D. Baggett by \_\_\_\_\_ (DEPUTY)  
(COUNTY OFFICIAL)

