

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

File # WEG
Index File #

History of original corner establishment:

Original corner set by Reuben R. Leigh
contract number 489 dated August 15, 1883

The government field notes state:

39.95 Set a basalt stone 12x10x8 ins 8 ins
in the ground for 1/4 Sec. cor.
marked 1/4 on N. face, and raised
a mound of stone 1 1/2 ft high 3 1/2
ft base alongside
pits impracticable

DIAGRAM
T18S R32E

$\frac{1}{4} \frac{10}{15}$

No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A Stone 12"x10"x8" in center of mound of deeply embeded stones. I located
several other corners in this area and by photogrammetric projection I determine
this corner to be harmonious with other corners in the area.

Description of monument and accessories I established to perpetuate
the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with
3-1/4" cap marked:
24 in ground & erected a mound of stones around
it.

I buried the original stone monument on the #5
side of the new monument flush with the ground.

from which I scribe NEW BEARING TREES:

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T18S R32E

$\frac{1}{4} \frac{S10}{S15}$

OPLS 1805
1980

CADASTRAL SURVEY
FOREST SERVICE

A 17" DBH PP Bears N28°E 4.5 ft., scribed 1/4 S10 BT
A 11" DBH PP Bears S3°E 10.0 ft., scribed 1/4 S15 BT

I painted faces & bands around BT's red & attached BT & Attention tags.
& nailed a brass washer to the new BT blaze marked PLS 1805.
Used steel tape & magnetic staff compass with 20° East variation, measuring
to the center of the new BT's.

This corner was set August 7, 1980

Witness: F.R. Palmer, and S.E. Trask

Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed
in this office for record on the 8th day of Sept, 1980
Robert D. Bazett by _____
(COUNTY OFFICIAL) (DEPUTY)

