


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None



Description of corner evidence found:

Nothing found.

Corner lies 32 ft. south and 28 ft. west of fence corner. Fence lines running north, south and west.

Description of monument and accessories established to perpetuate the original location of this corner:

On Aug. 18, 1983 at the calculated corner position I set a standard U.S. Forest Service all aluminum monument, 2 1/2" dia. x 30" high, with a 3" cap stamped:

Monument buried 24", 6" above the ground, no mound.

Set stl. fence post with boundary and land survey corner signs north of corner. Forest boundary posted north from corner.



New BT's

A 14" p.pine bears S.35°15'E., 33.9 ft. scribed "N1/16,S22,BT"

A 14" p. pine bears S.49°W., 22.4 ft. scribed "N1/16,S22,BT"

BT's have a 6" band of red paint, BT & attention signs, and a brass washer with "PLS 1287" at the base.

Witnesses: P. Zabala, M. Walker



Office of.....Surveyor.....County of.....Grant
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the...27... day of...Dec...1983
.....Robert D. Boyer..... by
(COUNTY OFFICIAL) (DEPUTY)