

CERTIFIED RECORD OF LAND CORNER MONUMENTATION**History of original corner establishment:**

Original GLO survey done by Rueben R. Leigh
under contract no. 489 dated Aug. 15, 1883.
Original field notes state:

40.00 Set a basalt stone 12x8x6 ins. 8 ins. in
the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W.
face from which

A pine 28 ins. diam. bears S.25°E., 146 lks dist.
marked $\frac{1}{4}$ SBT
A pine 40 ins. diam. bears N.80°W., 120 lks dist.
marked $\frac{1}{4}$ SBT

DIAGRAM

T18S R32E W.M.

 $\frac{1}{4}$

S 27

S 26

Grant Co., Ore.

Description of corner evidence found:

On Aug. 15, 1983 I found a 13x9x6 stone, with $\frac{1}{4}$ on west face, buried
8" in the ground, no mound, from which

A 40" pine stump bears N.66°W., 83.6 ft. and upon digging out rotten
portion at base I found "BT" still intact, with axe marks plainly
visible, and

A 30" pine stump bears S.30°30'E., 98.4 ft. with "BT" plainly visible
on broken, lower piece.

**Description of monument and accessories I established to perpetuate the
original location of this corner:**

On Aug. 15, 1983 at the location of the marked stone I set a standard
U.S. Forest Service all aluminum monument, 2 $\frac{1}{2}$ " dia. x 30" high, with
a 3" cap stamped:

Monument buried 14", 16" above the ground, in a
12" high x 30" dia. stone mound.

Original stone buried alongside.

Set a stl. fence post with attention sign alongside.



New BT's

A 16" p.pine bears S.42°20'E., 9.7 ft. scribed
" $\frac{1}{4}$ S26, BT"

A 6" p. pine bears N.30°40'W., 11.7 ft. scribed
" $\frac{1}{4}$ S27, BT"

BT's have a 6" band of red paint, BT & attention signs, and a
brass washer with "PLS 1287" at the base.

Witnesses: P. Zabala, M. Walker



Office of..... Surveyor..... County of..... Grant
State of..... Oregon..... I hereby certify that the within instrument was filed in this office
for record on the... 27... day of... Dec... 1983
Robert D. Baggett by.....
(COUNTY OFFICIAL) (DEPUTY)