


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally established by Frank W. Campbell under Contract No. 521 dated January 8, 1885. The notes state that at the corner a 10" x 8" x 7" notched basalt stone was set 7" in the ground from which:

- A 10" pine bears S 82° E, 182 Lks (120.1 ft) marked T7S R27E S9BT
- A 15" pine bears N 7° E, 119 Lks (78.5 ft) marked T7S R27E S4BT
- A 12" pine bears S 3° W, 178 Lks (117.5 ft) marked T7S R27E S8BT
- A 15" pine bears N 52° W, 96 Lks (63.4 ft) marked T7S R27E S5BT

Index No. E-9



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

The original stone was not re-covered. There was a small mound of stone 6' ± northwest of corner position re-established from bearing trees. Record distances from opposite BT centers would not intersect by 2 ft ±, set monument at the average position considering all original BT's.

From the re-established corner position:

- A 22" down-dead pine bears N 7° E, 80.3 ft, scribed T7S R27E S4BT
- A 19½" pine bears S 80° E, 121.1 ft with healed blaze
- A down-dead pine snag bears N 52° W, 64.1 ft scribed T7S R27E S5BT
- A 19" pine bears S 3½° W, 118.5 feet with visible scribing R27E S8B

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 9 inches in the ground and surrounded with a mound of stones to the cap.

Set steel fence post east and south of corner and attached signs 54-2 and 54-4 to one post and sign 54-2 to the other post.

Established 3 new BT's (original BT in southeast quadrant re-used)

- A 9" pine bears N 17½° E, 19.0 feet scribed T7S R27E S4BT
- A 9" pine bears S 57° W, 48.8 feet scribed T7S R27E S8BT
- A 9½" pine bears N 30° W, 24.8 feet scribed T7S R27E S5BT

New BT's have a lower blaze scribed BT with brass washer stamped PLS 1106 nailed flush. Attached signs 54-3 and 54-4 to all BT's and painted red ring around the trees above the upper blaze.

Used steel tape and magnetic compass with 19½° east declination. Measured to center of Bts.
See map of survey.


This corner set September 20, 1979

- Witnesses:
- D. Kaufman, PLS
 - G. Flowers, LSIT
 - B. English
 - B. Reynolds

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106



Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 15 day of Oct 1979
Robert D. Beget by _____
(COUNTY OFFICIAL) (DEPUTY)