


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. L-9

History of original corner establishment:

This corner was originally established by Frank W. Campbell under Contract No. 521 dated January 8, 1885. The notes state that at the corner a 14" x 8" x 6" marked basalt stone was set 9" in the ground and a mound of stone was raised alongside.



No record of subsequent remonumentation found in County Records .
Description of corner evidence found:

None. Corner re-established by single proportion measure.

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 12 inches in the ground and surrounded with a mound of stones to the cap.

Set steel fence post north of corner and attached signs 54-2 and 54-4.

Established 2 new BT's:

A 13 1/2" bull pine bears N 75° W, 108.9 feet scribed 1/4 S 17 BT

An 11" ponderosa pine bears N 84 1/2° E, 70.7 feet scribed 1/4 S 16 BT

* A 13 1/2" bull pine bears S 61° W, 27.0 feet scribing obliterated. This is not a BT.

New BT's have a lower blaze scribed BT with a brass washer stamped PLS 1106 nailed flush.

Attached signs 54-3 and 54-4 to all BT's and painted red ring around trees above upper blaze.

Used steel tape and magnetic compass with 19 1/2° east declination . Measured to center of Bts.
See map of survey.


This corner set October 3, 1979.

Witnesses: D. Kaufman, PLS
G. Flowers, LSIT

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106



Office of County Surveyor County of Grant
 State of Oregon , I hereby certify that the within Instrument was filed in this office
 for record on the 15 day of Oct 1979.
Robert D. Smith by _____
 (COUNTY OFFICIAL) (DEPUTY)