


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. P-9

History of original corner establishment:

This corner was originally established by Frank W. Campbell under Contract No. 521 dated January 8, 1885. The notes state that at the corner a 15" x 14" x 3" marked basalt stone was set 10" in the ground and a mound of stone was raised beside it.



No record of subsequent remonumentation found in County Records .  
Description of corner evidence found:

None. Corner was re-established by survey.

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 14 inches in the ground and surrounded with a mound of stones to the cap.

Set steel fence post north of corner and attached signs 54-2 and 54-4.

Established 2 new BT's:

A 12" pine bears N 45° W, 37.7 feet scribed 1/4 S 20 BT

A 9 1/2" juniper bears S 24 1/2° E, 63.9 feet scribed 1/4 S 21 BT

New BT's have a lower blaze scribed BT with a brass washer stamped PLS 1106 nailed flush.

Attached signs 54-3 and 54-4 to all BT's and painted red ring around trees above upper blaze.

Used steel tape and magnetic compass with 19 1/2° east declination . Measured to center of Bts.  
See map of survey.


This corner set September 18, 1979.

Witnesses: D. Kaufman, PLS  
G. Flowers, LSIT  
B. English  
B.J. Reynolds

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*William R. Wells*

OREGON  
JULY 22, 1977  
WILLIAM R. WELLS  
1106



Office of County Surveyor County of Grant  
State of Oregon , I hereby certify that the within Instrument was filed in this office  
for record on the 15 day of Oct 1979  
*Robert D. Dugan* by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)