


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. R-9

History of original corner establishment:

The corner was originally established by Frank W. Campbell under Contract No. 521 dated January 8, 1885. The original notes state that at the corner a 14" x 10" x 6" notched basalt stone was set 9" in the ground from which:

- A 6" pine bears N 44° E, 207 Lks (136.6 feet) marked T7S R27E S 21 BT
- A 9" pine bears S 8° E, 160 Lks (105.6 feet) marked T7S R27E S 28 BT
- A 48" pine bears S 40° W, 177 Lks (116.8 feet) marked T7S R27E S 29 BT
- A 12" pine bears N 54° W, 163 Lks (107.6 feet) marked T7S R27E S 20 BT



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

Found a small mound of stone which appear to be the broken remnants of the original stone from which:
 A 48" down and dead pine snag bears S 40° W 120.6 feet + to a stump hole scribed T7S R27E S29BT.
 An 18" down and dead pine snag bears S 13° E 105.6 feet + to stump hole scribed S 28.
 A pine with healed scar 14' long starting 5' above ground bears N 36½° E 167.1 feet with signs 54-3 and 54-4 attached (this is not an original BT).

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 8 inches in the ground and surrounded with a mound of stones to the cap.
 Set steel fence post north of corner and attached signs 54-2 and 54-4.
 Established 4 new BT's:

- An 11½" pine bears S 11½° W, 32.5 feet scribed T7S R27E S 29 BT
- A 16½" pine bears N 76½° W, 52.9 feet scribed T7S R27E S 20 BT
- A 16½" pine bears N 36½° E, 167.1 feet scribed T7S R27E S 21 BT
- An 11½" pine bears S 49° E, 70.5 feet scribed T7S R27E S 28 BT

New BT's have a lower blaze scribed BT with a brass washer stamped PLS 1106 nailed flush.
 Attached signs 54-3 and 54-4 to all BT's and painted a 6" red ring around BT's above upper blaze.

Used steel tape and magnetic compass with 19½° east declination . Measured to center of Bts.
 See map of survey .


This corner set September 17, 1979.

Witnesses: G. Flowers, LSIT
 B. Reynolds

REGISTERED PROFESSIONAL LAND SURVEYOR

William R. Wells

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106



Office of County Surveyor County of Grant
 State of Oregon , I hereby certify that the within Instrument was filed in this office
 for record on the 15 day of Oct 1979.
Robert D. Bazitt by _____
 (COUNTY OFFICIAL) (DEPUTY)