

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey
Section 29, T.7S., R.27E., W.M.

History of original corner establishment:

No record of previous monumentation.

DIAGRAM

T7S R27E
S29
SW-SW-NE
1/256

Description of corner evidence found:

None.

Description of monument and accessories established to perpetuate the original location of this corner:

At the corner point I set a 2 1/2" X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I built a stone mound around the monument.

S29
SW-SW-NE
1/256
PLS 1832
1986

From the corner:

- A Ponderosa Pine, 9" dia., N42°E, 42.8 ft. marked: SW SW NE 1/256 S29 BT
- A Ponderosa Pine, 9" dia., N70°W, 48.6 ft. marked: X at breast height and BT at base.

BTs have blaze and a 6" stripe painted red, a BT tag, a "Land Survey Monument" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 20°E.

April 13, 1986

Office of... *Surveyor* ... County of... *Grant* ...
 State of... *Oregon* ... hereby certify that the within instrument was filed in this office
 for record on the... *25* day of... *July* ... 19... *86*
Robert H. Dwyer by _____
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro

OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832