


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey
Section 29, T.7S., R.27E., W.M.

History of original corner establishment:

No record of previous monumentation.



Description of corner evidence found:

None.

Description of monument and accessories established to perpetuate the original location of this corner:

At the corner point I set a 2 1/2" X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I built a stone mound around the monument.

S29
C-S-S-SE
1/256
PLS 1832
1986

From the corner:

- A Douglas Fir, 12" dia., S88°E, 15.9 ft.
marked: C S S SE 1/256 S29 BT
- A Douglas Fir, 8" dia., S20°W, 26.6 ft.
marked: X at breast height and BT at base.
- A Douglas Fir, 17" dia., S33°E, 50.0 ft.
marked: C S S SE 1/256 S29 BT

BTs have blaze and a 6" stripe painted red, a BT tag, a "Land Survey Monument" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18 1/4°E.

April 18, 1986 // July 1, 1986 add BT.

Office of.....*Surveyor*..... County of.....*Grant*.....
 State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
 for record on the.....*25*..... day of.....*July*....., 19.....*86*
, by.....*Robert H. Deight*.....
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro
OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832