


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey
Section 29, T.7S., R.27E., W.M.

S-7

History of original corner establishment:

No record of previous monumentation.



Description of corner evidence found:

None.

Description of monument and accessories established to perpetuate the original location of this corner:

At the corner point I set a 2 1/2" X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

C

N1/16 | S29

C

PLS 1832
1986

From the corner:

- A Ponderosa Pine, 7" dia., N62°W, 26.3 ft.
marked: CN 1/16 S29 BT
- A Ponderosa Pine, 13" dia., N32 1/2°E, 53.5 ft.
marked: X at breast height and BT at base.
- A Ponderosa Pine, 16" dia., N12 1/4°W, 79.4 ft.
marked: CN 1/16 S29 BT

BTs have blaze and a 6" stripe painted red, a BT tag, a "Land Survey Monument" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18°E.

April 13, 1986 // July 1, 1986 add BT.

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 13 day of July, 1986
Robert D. Dyer by Fayette S. Munro
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro

OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832