


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey  
Section 29, T.7S., R.27E., W.M.

History of original corner establishment:

No record of previous monumentation.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

corner point fell in Wall Creek and I was unable to adequately monument it.

From the corner point:

A Reference Monument, 2 1/2" X 30" alum. pipe with a 3" alum. cap containing a magnet and marked: bears S30° 40' W, 121.80 ft.

A Reference Monument, 5/8" X 30" iron pin (rebar) with 1 1/2" dia. yellow plastic cap marked: PLS 1832 bears S21° 56' E, 129.82 ft.

A Ponderosa Pine, 48" dia., S16 1/4° W, 99.2 ft. marked: N S S 1/256 S29 BT

N-S-S  
1/256  
S29  
RM ↑  
121.8  
PLS 1832  
1986

BT has blaze and a 6" stripe painted red, a BT tag, a "Land Survey Monument" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There are 6' steel fence posts with "Land Survey Monument" signs within 5' of both RMs.

Measured to center of BT using theodolite and EDM.

April 10, 1986

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Fayette S. Munro*

OREGON  
JULY 13, 1979  
FAYETTE S. MUNRO  
1832

Office of *Surveyor* County of *Grant*  
State of *Oregon*, I hereby certify that the within instrument was filed in this office  
for record on the *25* day of *July*, 19*86*  
*Robert V. Dwyer* by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)