

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey  
Section 29, T.7S., R.27E., W.M.


T-5

History of original corner establishment:

Frank W. Campbell, under G.L.O. contract number 521, dated Jan. 8, 1885, set a basalt stone 16" X 8" X 6" eleven inches in the ground. Stone marked 1/4 on west face.

From the corner:

- A Pine, 10" dia., S20°E, 65 lks.
- A Pine, 24" dia., S64°W, 40 lks.



Description of corner evidence found:

I found no evidence of the original corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

At proportionate distance I set a 2 1/2" X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I built a stone mound around the monument.

T7S R27E  
1/4  
S30 | S29  
PLS 1832  
1986

From the corner:

- A Ponderosa Pine, 8" dia., S47°E, 26.6 ft. marked: 1/4 S29 BT
- A Ponderosa Pine, 23" dia., S42 1/2°W, 52.3 ft. marked: 1/2 S30 BT

BTs have blaze and a 6" stripe painted red, a BT tag, an "Attention" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with an "Attention" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 16 1/2°E.

April 12, 1986

Office of Sumner County of Grant  
 State of Oregon I hereby certify that the within instrument was filed in this office  
 for record on the 75 day of July, 1986  
Robert H. Dwyer (COUNTY OFFICIAL) Fayette S. Munro (DEPUTY)

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 13, 1979  
FAYETTE S. MUNRO  
1832