


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey
Section 29, T.7S., R.27E., W.M.

History of original corner establishment:

No record of previous monumentation.



Description of corner evidence found:

None.

Description of monument and accessories | established to perpetuate the original location of this corner:

At the corner point I set a 2 1/2" X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I built a stone mound around the monument.

S29
C-E-E-W
1/256
PLS 1832
1986

From the corner:

A Ponderosa Pine, 6" dia., S60°W, 39.2 ft.

marked: C E E W 1/256 S29 BT

A Ponderosa Pine, 8" dia., S89°E, 6.8 ft.

marked: X at breast height and BT at base.

A Ponderosa Pine, 9" dia., S43°W, 53.4 ft.

marked: C E E W 1/256 S29 BT

BTs have blaze and a 6" stripe painted red, a BT tag, a "Land Survey Monument" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18 1/2°E.

April 13, 1986 // July 1, 1986 add BT.

Office of... *Sumner* ... County of... *Grant* ...

State of... *Oregon* ... I hereby certify that the within instrument was filed in this office

for record on the... *25* day of... *July* ... 19... *86*

... *Robert D. Baggett* ... by ...

(COUNTY OFFICIAL)

(DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro
OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832