


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey
Section 29, T.7S., R.27E., W.M.

V-7

History of original corner establishment:

Frank W. Campbell, under G.L.O. contract number 521, dated Jan. 8, 1885, set a basalt stone 9" X 8" X 8" six inches in the ground. Stone marked $\frac{1}{4}$ on the north face.



From the corner:

A Fir, 36" dia., N50°W, 56 lks.
A Pine, 24" dia., S45°W, 52 lks.

Description of corner evidence found:

I found a stone 12" X 8" X 8", with no marks visible, in a small stone mound. From the corner:

- A Ponderosa Pine; down and rotted; approx. 18" dia.; with no scribing visible; root hole bears S46°W, 35 ft.
- A Douglas Fir; down and rotted; approx. 30" dia.; with no scribing visible; root hole bears N51°W, 39 ft.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the original corner point I set a 2 $\frac{1}{2}$ " X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I buried the original stone alongside.

T7S R27E
 $\frac{1}{4}$ $\frac{S29}{S32}$
 PLS 1832
 1986

From the corner:

- A Douglas Fir, 14" dia., S60°W, 7.3 ft.
marked: $\frac{1}{4}$ S32 BT
- A Ponderosa Pine, 8" dia., N19°W, 28.1 ft.
marked: $\frac{1}{4}$ S29 BT

BTs have blaze and a 6" stripe painted red, a BT tag, and an "Attention" sign. New BTs have, additionally, an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with an "Attention" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 17°E.

April 1, 1986

Office of Surveyor County of Grant
 State of Oregon I hereby certify that the within instrument was filed in this office
 for record on the 25 day of July, 1986
Robert D. Boyett BY Fayette S. Munro
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Fayette S. Munro

OREGON
 JULY 13, 1979
 FAYETTE S. MUNRO
 1832