


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. V-9

History of original corner establishment:

The corner was originally established by Frank W. Campbell under Contract No. 521 dated January 8, 1885. The original notes state that at the corner a 20" x 12" x 7" notched basalt stone was set 10" in the ground from which:

- An 8" pine bears N 25° E, 39 Lks (25.7 feet) marked T7S R27E S28BT
- A 12" pine bears S 17° E, 26 Lks (17.2 feet) marked T7S R27E S33BT
- A 7" pine bears S 45° W, 47 Lks (31.0 feet) marked T7S R27E S32BT
- A 20" pine bears N 16° W, 46 Lks (30.4 feet) marked T7S R27E S29BT



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

Found 10" x 12" x 7" stone buried. This stone appears to be the lower half of the original stone (top is broken off) from which:

- A 23" pine, dead but standing bears N 14° W, 30.0 feet with mostly healed blaze (R27E visible)
- A 15" pine (healthy) bears S 17° E, 18.6 feet marked T7S R27E S33BT

Also found the BT's with visible scribing for sections 32 and 28. Both of these BT's had slid down the hillside and no evidence remains of their original position.

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 8 inches in the ground and surrounded with a mound of stones to the cap.

Set steel fence posts north and east of corner and attached sign 54-2 to both posts and sign 54-4 to one post.

Established 3 new BT's: (healthy BT in Section 33 re-used)

- A 17½" red fir bears N 84° W, 55.7 feet scribed T7S R27E S29BT
- A 14" pine bears N 21° E, 41.6 feet scribed T7S R27E S28BT
- A 17" pine bears S 54° W, 33.8 feet scribed T7S R27E S32BT

New BT's have a lower blaze scribed BT with brass washer stamped PLS 1106 nailed flush.

Attached signs 54-3 and 54-4 to all BT's and painted red ring around the trees above the upper blaze.

Used steel tape and magnetic compass with 19½° east declination. Measured to center of Bts.

See map of survey .


This corner set September 17, 1979

Witnesses: G. Flowers, LSIT  
B. Reynolds

REGISTERED PROFESSIONAL LAND SURVEYOR
---

*William R. Wells*

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106
---



Office of County Surveyor County of Grant  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 15 day of Oct 1979  
*Robert D. Beyer* by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)